



CHANGZHOU UTEK COMPOSITE CO.,LTD.

Add: FuHan Yuan 1-812, New North District, Changzhou 213022, Jiangsu, China

Tel: 86-519-85856360 www.utekcomposite.com info@utekcomposite.com

Technical Data Sheet

Product Information: AR Glassfibre Chopped strand 18MM
ZrO₂ ≥16.7%

Application: For Cement or concrete reinforcement (GRC)

Test Condition: Temperature & Humidity 24°C 56%

| | | | |
|-----------------------------|----------------------------------------------|------------|------------------------------|
| Material properties: | 1、 Type of Glass | | Alkali Resiatant (AR) |
| | 2、 Zirconia (ZrO₂) content | % | ≥16.7 |
| | 3、 Filament dia | um | 13±2 |
| | 4、 Strand tex | Tex | 76±8 |

| | | | |
|------------------------|-----------------------------|--------------|----------------|
| Technical Data: | 1、 Colour | / | White |
| | 2、 Cut fiber length | mm | 18 |
| | 3、 Moisture content | % | ≤0.2 |
| | 4、 Sizing content | % | 0.8-2.0 |
| | 5、 Breaking strength | N/tex | ≥0.32 |

Packing details: 20kgs/kraft bag, 40bags/pallet, 800kgs/Pallet.

20 pallets/1*20'FCL. N.W.=16000kgs.

